

直接反射型光纖線



Model	Mode	Outline	Detectable object min.	Sensing distance	Amplifier	Operating temperature	Fiber material
FPR-51	M6 x P=0.75 1.0 ϕ x 2		0.03 ϕ	85mm	mF-06R or VF-06R	- 25°C ┆ + 70°C	Poly-plastic
FPR-52	M6 x P=0.75 1.0 ϕ x 1 0.25 ϕ x 15		0.03 ϕ	85mm			
FPR-53	M3 x P=0.5 0.5 ϕ x 2		0.03 ϕ	45mm			
FPR-54	M4 x P=0.7 0.5 ϕ x 2		0.03 ϕ	45mm			
FPR-55	M6 x P=0.75 1.0 ϕ x 2 Tube 2.5 ϕ		0.03 ϕ	85mm			
FPR-56	M4 x P=0.7 0.5 ϕ x 2 Tube 1.47 ϕ		0.03 ϕ	45mm			
FPR-57	4 ϕ x 10 0.5 ϕ x 2 Tube 1.47 ϕ		0.03 ϕ	45mm			
FPR-58	3 ϕ 0.5 ϕ x 2		0.03 ϕ	45mm			
FPR-59	M3xP=0.5 0.5 ϕ x 2 Tube 1.47 ϕ		0.03 ϕ	45mm			
FPR-60	4x10x15 1.0 ϕ x 2 Tube 2.5 ϕ		0.03 ϕ	85mm			
FPR-61	3x10x15 0.5 ϕ x 2 Tube 1.47 ϕ		0.03 ϕ	45mm			
FPR-62	4x20x7 1.0 ϕ x 2		0.03 ϕ	85mm			
FPR-63	3x13X7 0.5 ϕ x 2		0.03 ϕ	45mm			
FPR-64	M6 x P=0.75 1.0 ϕ x 2		0.03 ϕ	85mm			
FPR-65	M4 x P=0.7 0.5 ϕ x 2		0.03 ϕ	45mm			

對照型光纖線



Model	Mode	Outline	Detectable object min.	Sensing distance	Amplifier	Operating temperature	Fiber material
FPT-01	M4 x P=0.7 0.5Φ x 1		0.06 φ	120mm	mF-06R or VF-06R	- 25℃ ┆ + 70℃	Poly-plastic
FPT-02	M4 x P=0.7 1.0Φ x 1		0.1 φ	320mm			
FPT-03	M3 x P=0.5 0.5Φ x 1 Tube 0.9 φ		0.06 φ	120mm			
FPT-04	M4 x P=0.7 1.0Φ x 1 Tube 1.47 φ		0.1 φ	320mm			
FPT-05	M4 x P=0.7 0.5Φ x 1 Tube 1.47 φ		0.06 φ	120mm			
FPT-06	M3 x P=0.5 0.5Φ x 1		0.06 φ	120mm			
FPT-07	3.0Φ x 15 1.0Φ x 1		0.1 φ	320mm			
FPT-08	4Φx15.0 0.25Φ x 1		0.03 φ	60mm			
FPT-09	4x10x15 0.5 φ x 1 Tube 0.9 φ		0.06 φ	120mm			
FPT-10	4x10x15 1.0 φ x 1 Tube 1.47 φ		0.1 φ	320mm			
FPT-11	3x10x10 0.5 φ x 1		0.06 φ	120mm			
FPT-12	4x14x14 1.0 φ x 1		0.1 φ	320mm			
FPT-13	3x13x7 0.5 φ x 1		0.06 φ	120mm			
FPT-14	4x15x7 1.0 φ x 1		0.1 φ	320mm			
FPT-15	M4 x P=0.7 1.0 φ x 1		0.1 φ	320mm			